

PRESSURE GAUGES

DPF15E

A best seller in the control of filters obstruction : display, 1 relay, hour-counter.

The DPF15 is a differential manometer managed by a microprocessor, with high-brightness 3-digit display. It is a reliable, compact, digital, multifunctional product, with a competitive price if compared to the analog indicators. It features an internal temperature sensor which can optimize the measure of the pressure in different operating conditions. The DPF15 meets the requirements of controlling agencies because of the Dp and hour-counter functions.



PRODUCT CERTIFICATIONS

STANDARD



TECHNICAL SPECIFICATIONS

Main Features	Features	Values
Dimensions	External Dimensions (L x H x W mm)	105x105x57
Protection	Protection Level (standard)	IP56
Temperature	Working Temperature (°C)	-10... +50
Power Supply	Power Supply Range (standard)	115/230Vac 50-60Hz
	Power Supply Range (optional)	12/24/48Vdc 24Vac
	Power Consumption	2,5VA
Display	Display Type	7-segment display
	Resolution	3 digit
	Display Color (standard)	red
	Led	3
Inputs	Pressure Input	ok
	Pressure Range	-99/+999mmH2O
Outputs	Relay Outputs (nr)	1
	Relay Output Power	1A/24Vdc 0,5A/115Vac

DIMENSIONAL LAY-OUT

