

ENGINE PROTECTION

CPE

Small, simple, but with unique features: settable glow plug time and high rpm alarm.

Instrument with diameter 52 mm with 9 led indicators, easy to install and immediate reading. The alarms are: air filter, battery voltage, oil pressure, water temperature, fuel level, high speed alarm settable and plugs activation time settable, and a generic alarm. The reduced size, high speed alarm and plugs activation time settable make it unique in its kind. CPE includes a connector on back side that helps the electric cabling, and the 2A output relay allows an easy shutdown of the engine in case of activation of one or more alarms.



PRODUCT CERTIFICATIONS

STANDARD



TECNICAL SPECIFICATION

Features	Type	Description
Dimensions	External Dimensions (L x H x W mm)	Ø63x69
	Hole Dimensions (mm)	Ø52
Protection	Protection Level (standard)	IP65
Temperature	Working Temperature (°C)	-20...+70
	Storage Temperature (°C)	-30...+80
Power Supply	Power Supply Range (standard)	12Vdc/24Vdc
	Power Consumption (W)	1
Indicators	Led Indicators (nr)	9
Inputs	Digital Input (nr)	9
	Analog Input (nr)	2
	Alternator Input	ok
	Frequencymeter Input	ok
Outputs	Relay Outputs (nr)	4
	Relay Output Power	12V 1A

DIMENSIONAL LAY-OUT

