



## ELECTRIC VEHICLES

### ATS-25E

Controller for electric vehicles, with LCD monochrome display.

100mm diameter instruments equipped with 2 buttons for controller programming, 6 led bright signals and graphic display 128x64 pixel black/white amber backlight. It is complete of analogic and digital inputs, static and relay outputs; this allows a high flexibility of usage in various application fields, on any kind of electric vehicle.

☑ATS-25E includes CAN-BUS communication for connection with any electrical vehicle control device and battery management.

☑It is possible to customize the panel according to the needs of the customer.



### PRODUCT CERTIFICATIONS

STANDARD



### TECNICAL SPECIFICATION

Features	Type	Description
Dimensions	External Dimensions ( L x H x W mm )	Ø109x69
	Hole Dimensions (mm)	Ø100,5
Protection	Protection Level (standard)	IP65
Temperature	Working Temperature (°C)	-20...+70
	Storage Temperature (°C)	-30...+80
Power Supply	Power Supply Range (standard)	8 - 30 Vdc
Display	Display Type	monochrome LCD
	Display Dimensions ( L x H mm )	60x30
	Resolution	128x64
	Display Color (standard)	white
Indicators	Led Indicators (nr)	6
Inputs	Digital Input (nr)	10
Outputs	Relay Outputs (nr)	1
	Digital Output (nr)	3


**TECNICAL SPECIFICATION**

Features	Type	Description
Functions	Hour Counter	ok
Serial Ports	CAN	ok
Controls	Buttons (nr)	2



## DIMENSIONAL LAY-OUT

