

DISPLAY

MNTVIDEO

Operator panel 7" color with touch screen.



A 7" color display with touch screen, I/O for the interface with the different users and a keyboard with function buttons and commands for applications where the touch screen is difficult to use, make this panel suitable for various applications (operating machines, low motion vehicles, electric machines, etc..). There are digital inputs, a relay output, 4 positive static outputs and a W input. Operating panel MNTVIDEO includes 2 CAN BUS lines to simultaneously manage 2 types of protocols, for example it can manage a line in CAN OPEN with JOYSTICK, our module PWM, I/O module and the Inclinator, while with the other line in J1939 it can read the values of the engine.



PRODUCT CERTIFICATIONS

STANDARD



TECNICAL SPECIFICATION

Features	Type	Description
Dimensions	External Dimensions (L x H x W mm)	215x210x75
Protection	Protection Level (standard)	IP65
Temperature	Working Temperature (°C)	-20...+70
	Storage Temperature (°C)	-30...+80
Power Supply	Power Supply Range (standard)	8 - 30 Vdc
Display	Display Type	7.0" TFT
	Resolution	800x480
	Display Color (standard)	16bit RGB
Inputs	Digital Input (nr)	8
Outputs	Relay Outputs (nr)	1
	Digital Output (nr)	4
Functions	Hour Counter	ok
	Clock and Calendar	ok
Serial Ports	CAN	ok



TECNICAL SPECIFICATION

Features	Type	Description
Controls	Buttons (nr)	11
	Touch Screen	ok

DIMENSIONAL LAY-OUT

